

## SPECIFICATIONS

MODEL	POWER	BORE	CYLINDER		RAM SPEED		CAPACITY (TONS)	WEIGHT (LBS.)	SHIPPING DIMENSIONS		
			STROKE	ROD	PRESS	RETURN			L	W	H
FTP-100	5 HP 230 1 phase	8"	12"	6"	11 IPM	26 IPM	100	0,000	00"	00"	00"

Standard voltages available - please specify when ordering.  
Gasoline Powered also available.

## FORKLIFT TIRE PRESS 100 Ton

### STANDARD FEATURES

- ✓ **Large cylinder rod** provides platen stability and longer seal life.
- ✓ **Low pressure** hydraulic system maintains lower oil temperatures, resulting in higher efficiency and safer operation.
- ✓ **Double-acting** cylinder permits pressing as well as return.
- ✓ **Hydraulic power-lift** for vertical displacement of head assembly, 16" travel.
- ✓ **Cylinder activation** is fingertip controlled, the more the hand lever is engaged the more the ram movement is accelerated. This allows the operator to control the proper speed for the task.
- ✓ **Pressure regulator** to limit the ram pressure.
- ✓ **High capacity** 6 GAL. hydraulic oil reservoir.
- ✓ **All hydraulic and mechanical parts** are standard in the industry, and available throughout North America.

