

SPECIFICATIONS

MODEL NUMBER	POWER	TABLE	BORE	STROKE	RAM SPEED		CAPACITY (TONS)	WEIGHT (LBS.)	SHIPPING DIMENSIONS		
					PRESS	RETURN			L	W	H
GSP-100 46	10 HP 3 phase	48" x 72"	8"	12"	20 IPM	26 IPM	100	10,000	88"	108"	80"
GSP-100 48	10 HP 3 phase	48" x 96"	8"	12"	20 IPM	26 IPM	100	12,000	88"	132"	80"

Standard voltages available - please specify when ordering.

GANTRY STRAIGHTENING PRESS 100 Ton

STANDARD FEATURES

- ✓ **Powered movable workhead** for off-center work allows operator to position the cylinder from left to right and front to back with the touch of a lever.
- ✓ **Cylinder activation** is fingertip controlled, the more the hand lever is engaged the more the ram movement is accelerated. This allows the operator to control the proper speed for the task.
- ✓ **Pressure regulator** to limit the ram pressure.
- ✓ **Flat ram nose** can be easily changed to allow the user to adapt the press to a specific job.
- ✓ **Low pressure** hydraulic system maintains lower oil temperatures, resulting in higher efficiency and safer operation.
- ✓ **All hydraulic and mechanical parts are standard** in the industry, and available throughout North America.

