

SPECIFICATIONS HFBP-50 / 12 STD

PRESS	POWER	BORE	STROKE	RAM PRESS	SPEED RETURN	CAPACITY (TONS)	WEIGHT (LBS.)	SHIPPING DIMENSIONS L x W x H
HFP-50	5 HP 230 1 phase	7"	16"	18 IPM	22 IPM	50	2,900	48" 94" 104"
BP-12	Same	4"	20"	* 22.5 IPM	180 IPM	12	Same	Same

Standard voltages available - please specify when ordering.

H FRAME PRESS / BROACH PRESS 50 Ton / 12 Ton

STANDARD FEATURES


- ✓ **Electric / Hydraulic operation** provides smooth, consistent pressing action.
- ✓ **Open sides** to facilitate work on long pieces.
- ✓ **Flat ram nose** can be easily changed to allow the user to adapt the press to a specific job.
- ✓ **Quality Baldor motor**, low speed.
- ✓ **Low speed pump** - quiet, dependable operation.
- ✓ **Self-locking table design** eliminates lateral movement.
- ✓ **Double-acting cylinder** permits pulling as well as pressing ram action.
- ✓ **Hydraulic power-lift** for vertical displacement of table.
- ✓ **Pressure regulator** to limit the ram pressure.
- ✓ **Cylinder activation** is fingertip controlled, the more the hand lever is engaged the more the ram movement is accelerated. This allows the operator to control the proper speed for the task.
- ✓ **High capacity** 10 GAL. hydraulic oil reservoir.
- ✓ **Low pressure** hydraulic system maintains lower oil temperatures, resulting in higher efficiency and safer operation.
- ✓ **All hydraulic and mechanical parts are standard** in the industry, and available throughout North America.

STANDARD FEATURES 12 TON

- ✓ **Pressure regulator** to limit the ram pressure.
- ✓ **Speed control** limits the maximum speed of ram travel, allowing operator to select the proper speed for the task.
- ✓ * **Factory speed set to 22.5 IPM (OSHA STD).** Capable of up to 100 IPM. We recommend using proper safety guarding.

AVAILABLE OPTIONS 50 TON

- VB-50** V BLOCKS matched pair.
- FSG-50** Front safety guard for operator protection.
- FPS-50** Foot pedal-electric solenoid valve for hands-free operation, c/w electric control panel.
- ASC-50** Adjustable stroke control c/w foot pedal-electric solenoid valve, speed control and electric control panel.
- 7-24** 24 Inch stroke cylinder.
- SSE-50** Stop / Start c/w emergency stop button, wired direct to motor.



Custom designs available
We Build Them your Way!