

SPECIFICATIONS

MODEL NUMBER	POWER	BORE	STROKE	ROD	RAM SPEED PRESS	RAM SPEED RETURN	CAPACITY (TONS)	WEIGHT (LBS.)	SHIPPING DIMENSIONS L x W x H
HFP-50 MWH XW	5 HP 230 1 PH	7"	16"	3.0"	18 IPM	22 IPM	50	2,800	50" 90 108"

Standard voltages available - please specify when ordering.


H FRAME PRESS 50 Ton XW Powered Movable Workhead

STANDARD FEATURES

- ✓ **Electric / Hydraulic operation** provides smooth, consistent pressing action.
- ✓ **Open sides** to facilitate work on long pieces.
- ✓ **Flat ram nose** can be easily changed to allow the user to adapt the press to a specific job.
- ✓ **Quality motor**, low speed.
- ✓ **Low speed pump** - quiet, dependable operation.
- ✓ **Self-locking** table design eliminates lateral movement.
- ✓ **Powered movable workhead** for off-center work allows operator to position the cylinder from left to right with the touch of a lever.
- ✓ **Hydraulic power-lift** for vertical displacement of table.
- ✓ **Pressure regulator** to limit the ram pressure.
- ✓ **Cylinder activation** is fingertip controlled, the more the hand lever is engaged the more the ram movement is accelerated. This allows the operator to control the proper speed for the task.
- ✓ **High capacity** 15 GAL. hydraulic oil reservoir.
- ✓ **Low pressure** hydraulic system maintains lower oil temperatures, resulting in higher efficiency and safer operation.
- ✓ **All hydraulic and mechanical parts** are standard in the industry, and available throughout North America.

DIMENSIONS (INCHES)

MODEL	A	B	C	D	E	F
HFP-50 MWH XW	87	60	80	37	11	36



AVAILABLE OPTIONS

- VB-50** V BLOCKS matched pair.
- FSG-50** Front safety guard for operator protection.
- FPS-50** Foot pedal-electric solenoid valve for hands-free operation, c/w electric control panel.
- 7-24** 24 Inch stroke cylinder.
- SSE-50** Stop / Start c/w emergency stop button, wired direct to motor.

Custom designs available
We Build Them your Way!